

2K Topcoat

525/526 TPC-EPX						603 TPC-ACR						605 TPC-ACR					
2K Epoxid Topcoat						2K Acryl Topcoat						2K Acryl Topcoat					
St.	Zn	Al	Pl.	O.P.	S.G	St.	Zn	Al	Pl.	O.P.	S.U.	St.	Zn	Al	Pl.	O.P.	S.U.
																	
SC65-0703, SC65-0731						SC29-0863, SC29-0865, SC29-0885						SC29-0863, SC29-0885, SC29-0823					
SV32-0482						SV13-0732, SV13-0701, SV15-0339						SV13-0732, SV13-0701, SV15-0339					
glossy/satin glossy, good chemical resistance, good corrosion protection, direct adhesion to steel and concrete						glossy, good flow and very good weathering resistance						glossy, can be applied with brush and roll, good flow and very good weathering resistance					

648/650 TPC-PUR						656 TPC-PUR						729/732 TPC-ACR					
2K PUR Topcoat						2K PUR Topcoat						2K Acryl Topcoat					
St.	Zn	Al	Pl.	O.P.	S.U.	St.	Zn	Al	Pl.	O.P.	S.U.	St.	Zn	Al*	Pl.	O.P.	S.U.
 																	
SC29-0863, SC27-0500						SC29-0844, SC27-0500						SC29-0863, SC29-0885, SC29-0823					
SV13-0732, SV13-0701, SV15-0339						SV13-0732, SV13-0701, SV15-0339						SV13-0732, SV13-0701, SV15-0339					
glossy/satin glossy, good flow and good UV resistance, standard industry quality, certificate of compliance for dry foodstuff storing						glossy, efficient						glossy/mat, direct adhesion to many substrates, different gloss levels can be mixed					
												(*adhesion depends on aluminum alloy)					

730 TPC-ACR						900/901 TPC-ACR						902 TPC-ACR					
2K Acryl Topcoat						2K Acryl Topcoat, VOC						2K Acryl Topcoat, VOC					
St.	Zn	Al*	Pl.	O.P.	S.U.	St.	Zn	Al	Pl.	O.P.	S.U.	St.	Zn	Al	Pl.	O.P.	S.U.
												 					
SC29-0730, SC29-0863						SC29-0331						SC29-0823					
SV13-0732, SV13-0701, SV15-0339						SV13-0732, SV13-0701, SV15-0339						SV13-0701, SV15-0339					
satin glossy, direct adhesion to many substrates						glossy/satin glossy, good flow and very good weathering resistance, can be used for textured application						glossy, good flow and very good weathering resistance					
(*adhesion depends on aluminum alloy)																	

Explanation

Product	Product
Product name	product name
Substrate	St. Zn Al* Pl. O.P. S.U.
Compliance	   
Hardener	SC00-0000, SC00-0000
Thinner	SV00-0000, SV00-0000, SV00-0000
Remarks	satin glossy, smooth and textured application, very good sagging resistance, high film thicknesses can be applied (*adhesion depends on aluminum alloy)

Substrate	
St.	Steel
Zn	Zink
Al	Aluminium
Pl.	Plastics
O.P.	Old Paintwork
S.U.	Salcomix Undercoats

Symbols	
	VOC compliant
	Corrosion classification acc. to DIN EN ISO 12944
	Airless / Airmix Application
	Low flame spread

www.salcomix.com